## a) Tracking performance:

- Document the assumption on the simulation model that has been used, such as physics processes and detector simulations besides hand-calculations.
- Show the hit efficiency for each tracking layer in central Au+Au (sqrt(s)=200GeV) and p+p (sqrt(s)=200/500GeV) collisions a) for tracking from outside to inside with the existing PHENIX central tracking detector and b) from inside to outside without the existing PHENIX central tracking detector.
- What is the level of S/N for the strip-pixel system that is acceptable for the tracking with and without the central PHENIX tracking system?

## b) VTX material budget:

- Document the level of details that has been included for each tracking layer and the mechanical support structure.
- To what extent has the impact of albedo particles been taken into account in simulations, such as albedo particles from the NCC?
- Show the VTX material budget as a function of pseudo-rapidity and azimuthal angle.
- What is the VTX material budget that is tolerable by the PHENIX collaboration as a whole: J/psi program, non-photonic electrons and DCA resolution necessary for a successful discrimination of charm / bottom? It appears that the total material budget for the current VTX design is ~16% X0. This is an issue that has to be addressed as soon as possible to allow for potential re-direction of efforts on the actual VTX layout for layer 3/4.

- c) Photon-jet measurements / Jet measurements:
- What is the resolution of the jet pseudo-rapidity for jets for which only the VTX is used? How does this change when including the existing central tracking system? How is this dependent on pT in particular for the case of VTX only tracking?
- What is the pT reach of jet reconstruction in general for VTX only tracking?
- What is the efficiency for photon-jet reconstruction and therefore the impact on the accuracy of various observable measurements involving photon-jet measurements for an assumed integrated luminosity?

## d) Heavy-flavor measurements:

- How is the DCA value of 50 mkm justified for various heavy-flavor measurements? What drives this number? How well can charm and bottom events really be separated?
- What is the status of the DCA resolution studies using the full VTX material thickness?
- Demonstrate the level of semi-leptonic electron reconstruction taking into account the impact of material thickness giving rise to conversion background.
- What is the efficiency for heavy-flavor type measurement and therefore what is the accuracy of various observable measurements for an assumed integrated luminosity such as RAA and v2 in Au-Au and d-Au collisions and ALL in polarized p-p collisions?